#5 105 10-2501

Attorney Docket No. 1568.1012/MDS/JGM

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent Application of:)
Tae-kyoung KANG, et al.) Crown Art Unit: Not assigned
Application No.: Not assigned) Group Art Unit: Not assigned)
Filed: April 24, 2001) Examiner: Not assigned)
For: PLASMA DISPLAY PANEL AND METHO THEREOF	D OF MANUFACTURING PARTITIONS

INFORMATION DISCLOSURE STATEMENT

Assistant Commissioner for Patents Washington, D.C. 20231

Sir:

In accordance with the duty of disclosure provisions of 37 CFR §1.56, there is hereby provided certain information which the Examiner may consider material to the examination of the subject U.S. patent application. It is requested that the Examiner make this information of record if it is deemed material to the examination of the subject application.

1.	Enclosures accompanying this Information Disclosure Statement are:		
	1a.	[X]	Form PTO-1449.
	1b.	[X]	Copies of IDS citations.
	1c.	[]	An English language copy of search report(s) from a counterpart foreign application or a PCT International Search Report.
	1d.	[X]	English language translation (abstract only) attached to each non-English language publication.
	1e.	[X]	Explanations of Relevancy of References (ATTACHMENT 1(e), hereto) for providing a concise explanation of each non-English publication.
	1f.	[]	List of Copending Applications (ATTACHMENT 1(f), hereto).
	1g.	[]	List of Additional Submitted Documents (ATTACHMENT 1(g), hereto).

2. [X] In accordance with 37 CFR §1.98, a concise explanation of what is presently understood to be the relevance of each non-English language publication is:

(Check appropriate Items 2a, 2b, 2c and/or 2d)

- 2a. [] satisfied because all non-English language publications were cited on the enclosed English language copy of the PCT International Search Report or the search report from a counterpart foreign application indicating the degree of relevance found by the foreign office. (See U.S. Patent & Trademark Office's authorization in the Federal Register, Vol. 57, No. 12, January 17, 1992, at page 2031 (Reply to Comment 68).)
- 2b. [] set forth in the application.
- 2c. [X] satisfied because an English language translation (abstract only) is attached to each non-English language publication.

By:

- 2d. [X] enclosed as Attachment 1(e), hereto.
- 3. No admission is made that the information cited in this Statement is, or is considered to be, material to patentability nor a representation that a search has been made (other than search report(s) from a counterpart foreign application or a PCT International Search Report, if submitted herewith). 37 CFR §§ 1.97(g) and (h).

Respectfully submitted,

STAAS & HALSEY LLP

700 Eleventh Street, N.W., Suite 500

Washington, D.C. 20001 Telephone: (202) 434-1500 Facsimile: (202) 434-1501 Michael D. Stein Registration No. 37,240

ATTACHMENT 1(e)

Not assigned ^a

	TITACIMIENT I(C)
ATTORNEY DOCKET NO.	APPLICATION NO.
1568.1012/MDS/JGM	Not assigned
FIRST NAMED INVENTOR	
Tae-kyoung KANG, et al.	
FILING DATE	GROUP ART UNIT 2

EXPLANATIONS OF RELEVANCY OF REFERENCES

1) Japanese Patent Publication No. 08-255574 is an example of a plurality of dummy electrodes formed parallel to an address electrode at a portion corresponding to the outermost portion of a display area. The dummy electrodes are electrically connected to one another to be connected in common with an external connection terminal

April 24, 2001

- 2) Japanese Patent Publication No. 11-185634 is an example of a dummy electrode formed parallel to an address electrode at a portion corresponding to the outermost portion of a display area. The outermost address electrode and the dummy electrode are electrically connected to each other.
- 3) Japanese Patent Publication No. 11-296139 is an example of a plurality of dummy electrodes formed parallel to an address electrode at a portion corresponding to the outermost portion of a display area. The outermost address electrode and the dummy electrode are electrically connected to each other. A predetermined voltage is applied to the outermost address electrode during a priming discharge period, an address discharge period, and a sustain discharge period.